

Tapeta na flizelinie z kolorowym nadrukiem - Typ21



Producent:

Pracownia Dekoracji AKATJA Katarzyna Kwiel
26-200 Końskie ul. Różana 35 email: akatja@akatja.pl

Zamierzone zastosowanie:

Tapeta z kolorowym nadrukiem do naklejania wewnątrz budynków na suchych, gładkich, prostych ścianach za pomocą kleju do tapet ciężkich.

Instrukcja montażu:

Tapetę naklejać zgodnie z instrukcją naklejania kleju do tapet w pomieszczeniach suchych, nie narażonych na nadmierną wilgoć. Do naklejania używać osobno kupionego kleju do tapet ciężkich.

Instrukcja używania i konserwacji:

Tapetę w razie potrzeby można delikatnie przetrzeć miękką wilgotną szmatką z łagodnymi środkami myjącymi. Nie używać substancji żrących, wybielaczy, rozpuszczalników.

Instrukcja utylizacji:

Tapetę po okresie użytkowania wyrzucać zależnie od miejscowych przepisów zagospodarowania odpadów - do pojemnika na odpady remontowe, budowlane, oddać do PSZOK. Tapeta niezależnie od rodzaju posiada kod 17 09 04.

Ostrzeżenia:

Producent na podstawie wieloletnich obserwacji własnych i Klientów stwierdza, że produkt jest bezpieczny w przypadku stosowania w dających się racjonalnie przewidzieć warunkach.

Dokumentacja techniczna:

Tapeta została wyprodukowana przy użyciu poniższych materiałów:

- tkanina tapetowa – Ikonos WallArt
- atrament – Mutoh UMS

Proces produkcyjny w żadnym stopniu nie zmienia właściwości, bezpieczeństwa powyższych materiałów. Producenci i dystrybutorzy powyższych materiałów deklarują, że są one bezpieczne i nadają się do zastosowania w niniejszym produkcie.

Na kolejnych stronach znajduje się dokumentacja techniczna udostępniona przez producentów w/w materiałów.

CERTIFICATE OF COMPLIANCE



MUTOH INDUSTRIES
LTD
UMS21

311321-420
Certificate Number
16 Oct 2023 - 16 Nov 2024
Certificate Period
Certified
Status

UL 2818 - 2022 Gold Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Wall finishes are determined compliant. In accordance with California Department of Public Health (CDPH) Standard Method V1.2-2017 using a Classroom Environment with an air change of 0.82 hr⁻¹ and a loading of 94.60 m²; and Wall finishes are determined compliant. In accordance with California Department of Public Health (CDPH) Standard Method V1.2-2017 using an Office Environment with an air change of 0.68 hr⁻¹ and a loading of 33.40 m².

Product tested in accordance with UL 2821 test method to show compliance to emission limits on UL 2818. Section 7.1 and 7.2.



UL investigated representative samples of the Identified Product(s) to the Identified Standard(s) or other requirements in accordance with the agreements and any applicable program service terms in place between UL and the Certificate Holder (collectively "Agreement"). The Certificate Holder is authorized to use the UL Mark for the Identified Product(s) manufactured at the production site(s) covered by the UL Test Report, in accordance with the terms of the Agreement. This Certificate is valid for the identified dates unless there is non-compliance with the Agreement.

GREENGUARD Gold Certification Criteria for Building Products and Interior Finishes

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC ^(A)	-	0.22	mg/m ³
Formaldehyde	50-00-0	9 (7.3 ppb)	µg/m ³
Total Aldehydes ^(B)	-	0.043	ppm
4-Phenylcyclohexene	4994-16-5	6.5	µg/m ³
Particle Matter less than 10 µm ^(C)	-	20	µg/m ³
1-Methyl-2-pyrrolidinone ^(D)	872-50-4	160	µg/m ³
Individual VOCs ^(E)	-	1/2 CREL or 1/100th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C₆ – C₁₀ range, with responses calibrated to a toluene surrogate. Maximum allowable predicted TVOC concentrations for GREENGUARD Gold (0.22 mg/m³) fall in the range of 0.5 mg/m³ or less, as specified in CDPH Standard Method v1.2.

(B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

(C) Particle emission requirement only applicable to HVAC Duct Products with exposed surface area in air streams (a forced air test with specific test method) and for wood finishing (sanding) systems.

(D) Based on the CA Prop 65 Maximum Allowable Dose Level for inhalation of 3,200 µg/day and an inhalation rate of 20 m³/day

(E) Allowable levels for chemicals not listed are derived from the lower of 1/2 the California Office of Environmental Health Hazard Assessment (OEHHA) Chronic Reference Exposure Level (CREL) as required per the CDPH/EHLB/Standard Method v1.2 and BIFMA level credit 7.6.2 and 1/100th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



Technical Data Sheet

Product: WALL-ART

Version Number 1.1

Revision Date 12.10.2015

Page 1/1

Product: WALL-ART

Producer/supplier: Atrium Centrum Ploterowe Sp. z o.o.

Properties:

Patterns: FROSTED, WOOD, SMOOTH, MOZAIK,
ROCK, BLAZE, CANVAS, STONE, SALT, LEATHER

Color:	White
Odor:	No
Roll width:	1.07m
Roll lenght:	50m/70m
Core diameter:	76 mm
Weight:	
Non woven:	~ 65g/m ²
Coating – plasticized PVC:	~ 200g/m ²
Thickness:	0.35 – 0.6 mm
Fire resistance:	C-s2, d 0 class in according to ISO 13501-1
Indoor suitability ranking:	AgBB/DIBt certification and class A+

Application:

Digital printing using eco-solvent inks. Chemical composition optimized for BALANCE ECO and BALANCE ECO FAST inks;
Suitable for all solvent, UV and Latex printers.

Additional recommendations:

Recommended storage temperature: between +5°C and 40°C.
For good process ability printing should be done at room temperature:
between +15°C and +35°C.