

Kolorowy wydruk na grubym papierze z laminatem - Typ25



Producent:

Pracownia Dekoracji AKATJA Katarzyna Kwiel
26-200 Końskie ul. Różana 35 email: akatja@akatja.pl

Zamierzone zastosowanie:

Wydruki przeznaczone do umieszczeniu na różnym podłożu wewnątrz pomieszczeń np. szyba, tablica korkowa, tkanina, płyta meblowa, ściana itp. za pomocą np. taśmy klejącej, szpilek, pinesek, zszywek itp. lub do oprawienia w ramy, antyramy – w zależności od potrzeb Klienta jako dekoracja, informacja, reklama.

Instrukcja montażu:

Wydruki po rozwinięciu są gotowe do używania, montaż według własnej inwencji i potrzeb Klienta.

Instrukcja używania i konserwacji:

Wydruki użytkować w miarę możliwości w suchych warunkach, aby papier nie uległ rozmięknieniu, z daleka od otwartego ognia.

Instrukcja utylizacji:

Wydruk po okresie użytkowania wyrzucać do pojemnika na segregowany papier.

Ostrzeżenia:

Przy normalnym użytkowaniu, producent na podstawie wieloletnich obserwacji własnych i Klientów stwierdza, że produkt jest bezpieczny w przypadku stosowania w dających się racjonalnie przewidzieć warunkach.

Dokumentacja techniczna:

Wydruk został wyprodukowany przy użyciu poniższych materiałów:

- papier gruby – papier plakatowy Ikonos Poster pro WB 200g

- atrament – Mutoh UMS

- laminat błyszczący lub matowy -Ikonos Profiflex Lam-Pro GPT L80+/ MPT L80+

Proces produkcyjny w żadnym stopniu nie zmienia właściwości, bezpieczeństwa powyższych materiałów. Producenci i dystrybutorzy powyższych materiałów deklarują, że są one bezpieczne i nadają się do zastosowania w niniejszym produkcie.

Na kolejnych stronach znajduje się dokumentacja techniczna udostępniona przez producentów w/w materiałów.

CERTIFICATE OF COMPLIANCE



MUTOH INDUSTRIES
LTD
UMS21

311321-420

Certificate Number

16 Oct 2023 - 16 Nov 2024

Certificate Period

Certified

Status

UL 2818 - 2022 Gold Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Wall finishes are determined compliant in accordance with California Department of Public Health (CDPH) Standard Method V1.2-2017 using a Classroom Environment with an air change of 0.82 hr⁻¹ and a loading of 94.60 m², and Wall finishes are determined compliant in accordance with California Department of Public Health (CDPH) Standard Method V1.2-2017 using an Office Environment with an air change of 0.68 hr⁻¹ and a loading of 33.40 m².

Product tested in accordance with UL 2821 test method to show compliance to emission limits on UL 2818, Section 7.1 and 7.2.



UL investigated representative samples of the identified Product(s) to the identified Standard(s) or other requirements in accordance with the agreements and any applicable program service terms in place between UL and the Certificate Holder (collectively "Agreement"). The Certificate Holder is authorized to use the UL Mark for the identified Product(s) manufactured at the production site(s) covered by the UL Test Report, in accordance with the terms of the Agreement. This Certificate is valid for the identified dates unless there is non-compliance with the Agreement.

GREENGUARD Gold Certification Criteria for Building Products and Interior Finishes

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC ^(A)	-	0.22	mg/m ³
Formaldehyde	50-00-0	9 (7.3 ppb)	µg/m ³
Total Aldehydes ^(B)	-	0.043	ppm
4-Phenylcyclohexene	4994-16-5	6.5	µg/m ³
Particle Matter less than 10 µm ^(C)	-	20	µg/m ³
1-Methyl-2-pyrrolidinone ^(D)	872-50-4	160	µg/m ³
Individual VOCs ^(E)	-	1/2 CREL or 1/100th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C₆ – C₁₀ range, with responses calibrated to a toluene surrogate. Maximum allowable predicted TVOC concentrations for GREENGUARD Gold (0.22 mg/m³) fall in the range of 0.5 mg/m³ or less, as specified in CDPH Standard Method v1.2.

(B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

(C) Particle emission requirement only applicable to HVAC Duct Products with exposed surface area in air streams (a forced air test with specific test method) and for wood finishing (sanding) systems.

(D) Based on the CA Prop 65 Maximum Allowable Dose Level for inhalation of 3,200 µg/day and an inhalation rate of 20 m³/day

(E) Allowable levels for chemicals not listed are derived from the lower of 1/2 the California Office of Environmental Health Hazard Assessment (OEHHA) Chronic Reference Exposure Level (CREL) as required per the CDPH/EHLB/Standard Method v1.2 and BIFMA level credit 7.6.2 and 1/100th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



UL investigated representative samples of the Identified Product(s) to the Identified Standard(s) or other requirements in accordance with the agreements and any applicable program service terms in place between UL and the Certificate Holder (collectively "Agreement"). The Certificate Holder is authorized to use the UL Mark for the Identified Product(s) manufactured at the production site(s) covered by the UL Test Report, in accordance with the terms of the Agreement. This Certificate is valid for the identified dates unless there is non-compliance with the Agreement.





POSTER PAPER PRO 200 MATT

matt 3672, 200 g/m²

Matowy papier plakatowy o wysokiej sztywności do zastosowań zewnętrznych i wewnętrznych

Ten wielowarstwowy, odporny na działanie czynników atmosferycznych papier o wysokiej wytrzymałości i matowym wykończeniu nadaje się do druku farbami rozpuszczalnikowymi, lateksowymi i UV. Wydruki imponują jednolitym obrazem drukowanym i dobrą odpornością na zarysowania. Papier plakatowy Pro kwalifikuje się do zastosowania w zewnętrznej fakturze reklamowej. Ciężar 200 g/m² zapewnia materiałowi wysoką nieprzezroczystość i sztywność, a tym samym umożliwia optymalne prowadzenie.

Technologie



Właściwości



Cechy

- Jednorodny obraz wydrukowany
- Powierzchnia wodoodporna
- Wysoka sztywność

Wskazówki

- Prosimy zwrócić uwagę podczas drukowania dowolną drukarką HP Latex serii 300, aby drukować rolkę na rolkę!
- Ilość farby należy dopasować do papieru. Proszę zmniejszyć pojedyncze kolory cyjan, magenta, żółty i czarny (ograniczenia dotyczące tuszu) oraz zmniejszyć maksymalną ilość atramentu (tuszu). Pomoże to obniżyć koszty farb drukarskich i poprawić wydajność suszenia.
- Należy postępować zgodnie z zaleceniami producenta drukarki i tuszu. Temperatura podgrzewania i suszenia powinna być wcześniej sprawdzona, aby upewnić się, że uzyskano pożądany efekt
- W celu zachowania wysokiej jakości papieru należy go przechowywać i przetwarzać w klimacie o wilgotności względnej 30-65 % i temperaturze 10-30°C (50-86°F). Hartowanie lateksowe / IR
- Atrament nie jest w pełni wodoodporny.

Dane techniczne

Name	Wartość	Normy
Waga [g/m ²]	200	ISO 536
Grubość (total) [µm]	220	ISO 534
Nieprzezroczystość [%]	>98	ISO 2471
Błysk (85°)	18	ISO 2813
Chromatyczność (D50/2°) M0	L* 93.0 / a* 1.4 / b* -6.8	ISO 13655, M0

The values stated above are only for orientation. Before using our print media please check its compatibility for your printer and the intended application. We cannot be held responsible for any mistakes resulting from technically modified printers and/ or inks. Product design changes to our products technical developments may be carried out without prior notice.



NARODOWY INSTYTUT ZDROWIA PUBLICZNEGO PZH
– Państwowy Instytut Badawczy
National Institute of Public Health NIH – National Research Institute

ATEST HIGIENICZNY

B.BK.60111.0789.2022

HYGIENIC CERTIFICATE

ORYGINAŁ

NATIONAL INSTITUTE OF PUBLIC HEALTH NIH – NATIONAL RESEARCH INSTITUTE

Wyrób / product: **Laminaty IKONOS PROFIFLEX LAM-PRO**

Zawierający / containing: poli(chlorek winylu), stabilizator barowo-cynkowy i inne składniki wg dokumentacji producenta

Przeznaczony do / destined: ochrony wydruków wielkoformatowych stosowanych w miejscach użyteczności publicznej np. centrach handlowych, hotelach, restauracjach, szkołach, przedszkolach itp.

Wymieniony wyżej produkt odpowiada wymaganiom higienicznym przy spełnieniu następujących warunków
/ the above-named product is acceptable according to hygienic criteria with the following conditions:

Zastosowanie wyrobu musi być zgodne z zaleceniami producenta oraz aktualnymi przepisami dotyczącymi obiektu, w którym ma on być używany. Na opakowaniu należy umieścić etykietę w języku polskim, zawierającą zalecenia dotyczące środków ostrożności wg karty charakterystyki wyrobu, zgodnie z obowiązującymi przepisami prawnymi. Wyrób należy przechowywać w miejscu niedostępnym dla dzieci. Atest higieniczny nie dotyczy parametrów technicznych, walorów użytkowych i oceny właściwości alergizujących wyrobu.

Wytwórca / producer:

ATRIUM Centrum Plotkowe Sp. z o.o.
45-446 Opole
ul. Gosińska 2d, Polska

Niniejszy dokument wydano na wniosek / this certificate issued for:

ATRIUM Centrum Plotkowe Sp. z o.o.
45-446 Opole
ul. Gosińska 2d, Polska



Atest może być zmieniony lub unieważniony po przedstawieniu stosownych dowodów przez którąkolwiek stronę. Niniejszy atest traci ważność po 2028.02.13 lub w przypadku zmian w recepturze albo w technologii wytwarzania wyrobu.

The certificate may be corrected or cancelled after appropriate motivation. The certificate loses its validity after 2028.02.13 or in the case of changes in composition or in technology of production.

Data wydania atestu higienicznego: 13 lutego 2023

The date of issue of the certificate: 13th February 2023

Kierownik
Zakładu Bezpieczeństwa Zdrowotnego
Środowiska

2 mp. M. Jolanta Solecka
dr hab. Jolanta Solecka, prof. NIZP PZH-PIB

Kontakt w sprawie niniejszego atestu higienicznego / To contact regarding this hygienic certificate
Zakład Bezpieczeństwa Zdrowotnego Środowiska NIZP PZH - PIB / Department of Environmental Health and Safety NIPH NIH - NRI
00-791 Warszawa, ul. Chocimska 24 / 00-791 Warsaw, Chocimska 24, Poland
e-mail: sekretariat-bk@pzh.gov.pl tel. +48 22 54-21-354, +48 22 54-21-349

IKONOS PROFIFLEX LAM-PRO GPT L80+ (GLOSSY) / MPT L80+ (MATT)

PRODUCT DESCRIPTION:

Ikonos Profiflex Lam-Pro Series includes monomeric, transparent, glossy (GPT L80+) or matt (MPT L80+) overlamination PVC films with UV adsorber. Materials intensifying the colour range of an image and significantly extending its durability. Profiflex Lam-Pro GPT L80+/MPT L80+ reduce colour fading and effectively retards printout deterioration caused by weather conditions.

PRODUCT STRUCTURE:

Film: 70 mic, transparent, glossy or matt, monomeric PVC

Adhesive: permanent, transparent, water-based dispersion of polyacrylate

Liner: one-side siliconized, clay coated paper, 121 gsm

RANGE OF APPLICATION: Ikonos Profiflex Lam-Pro GPT L80+ and MPT L80+ protect pictures and images from mechanical damage, moisture and UV radiation. They are perfect solution for any kind of indoor applications as well as for short- and midterm outdoor usage.

PHYSICAL FEATURES:

	STANDARD NO.	VALUE
Thickness		
Thickness of PVC	ISO 2286-3	70 mic (±5%)
Total thickness (film+glue+liner)	ISO 2286-3	198 mic (±10%)
Tensile stress at break		
Along	ISO 527-3/2/200	20 MPa
Initial	ISO 527-3/2/200	15 MPa
Tensile strain at break		
Along	ISO 527-3/2/200	160%
Initial	ISO 527-3/2/200	160%
Adhesive Power		
Initial	FINAT 9	8.8 N/25 mm
After 20 min	FINAT 1	13.3 N/25 mm
After 24 h	FINAT 1	19.8 N/25 mm
Temperature range		
While applying	-	from 10°C to 33°C
While exploiting	-	from 10°C to 30°C
Flammability	Adhered to aluminium, glass or steel – self-extinguishing*	
Durability	90° vertical exposure	indoor 5 years (unprinted)
	90° vertical exposure	outdoor 2 years (unprinted)
Shelf Life	2 years (in original packaging, at 20 °C and 50% relative humidity)	

* Producer's internal test method

GENERAL CHARACTERISTICS OF THE PRODUCT

All IKONOS products are subject to quality control throughout the entire manufacturing process, are covered with a commercial quality warranty and are free of any manufacturing defects. Any published information on IKONOS products is based on research which the manufacturer deems reliable, even though this information is not considered a warranty. The Manufacturer/Supplier confirms the specific scope of use of the product, provided the Buyer strictly complies with all recommendations.

The Manufacturer/Supplier shall not guarantee the full scope of use of the product if:

- the Buyer fails to comply with the recommendations of the Manufacturer/Supplier or its instructions;
- the material is subject to mechanical damage or it loses its physical and chemical characteristics or its resistance, e.g. water resistance, UV resistance, etc. due to incorrect application of the material;
- the material is processed, e.g. printed on, combined with another material, subject to physical and chemical treatment, etc.;
- the material has been affected by mechanical force or is used incorrectly;
- the material has been misused.

The Buyer shall use the material only in properly prepared and dedicated locations, the Buyer shall use all materials strictly according to their intended use. In case of some applications/locations, the material may be subject to increased wear and tear rate or may lose its physical and chemical properties.

PRODUCT LIFE

The Supplier guarantees product life provided all rules described above are adhered to and subject to the following conditions. The data included in the product data sheet applies to a vertical display of a non-printed/unprocessed product. Outdoor product life applies to moderate climate of Central Europe. The Manufacturer/Supplier recommends using solvent glue for outdoor applications. In the event the product is subject to extreme weather conditions, e.g. strong sunlight, high levels of humidity or intensive UV radiation, degradation at an increased rate may occur. In case of some applications/locations, the material may be subject to increased wear and tear rate or may lose its physical and chemical properties. The strength of a PVC film may also be reduced in areas characterised by high pollution levels and at high altitudes. The Buyer shall use the material only in properly prepared and dedicated locations/on properly prepared and dedicated surfaces. The Buyer shall use all materials only as intended.

USE, STORAGE AND PROCESSING OF THE PRODUCT

NOTE:

THE PRODUCT/MATERIAL is subject to the above-mentioned rules in terms of its original intended use. DO NOT use the material for any purposes other than those indicated by the Manufacturer/Supplier. The Customer shall be fully responsible for any misuse of the material and/or failing to comply with the recommendations of the Manufacturer/Supplier. Any explicit or implied assurances or declarations of the Manufacturer/Supplier shall not be legally binding if the Product/Material is misused.

APPROPRIATE TRANSPORT

The Supplier shall become familiar with the recommended transportation conditions (particularly in terms of temperature, humidity, arrangement of the product on the pallet and the number of packaging layers).

APPROPRIATE STORAGE

The Supplier hereby indicates that appropriate storage is vital for the life of the product. Recommended storage conditions: relative humidity of 50%, 20°C in the original packaging. The Customer shall store the rolls with the label containing the information on the product type, dimensions of the roll and the batch number. Any complaints shall be accepted only if the batch number is indicated. Edges of the PVC film may be subject to shrinkage during storage. For best printing quality/processing results, we recommend storing rolls for at least 24 hours, prior to printing/processing, in the room where the printing/processing is to be done. Large temperature and humidity difference between the room and the material may cause material rippling and may affect printing quality. Once the material has been printed on, the ink must become completely dry prior to any further processing of the material, e.g. laminating or application. Any solvent residues may cause a change in the characteristics of the product. The surface on which the product is to be applied must be free of dust, grease, lubricants and other substances, which may negatively affect the adhesion of the material. Due to the wide range of possible applications, the Customer shall, on each occasion, make sure the given material fully corresponds to their needs. We recommend conducting individual tests prior to each application. As IKONOS products are suitable for a wide range of applications and are constantly developed, the Buyer should always test the given product in terms of the intended application.

LOSS OF WARRANTY/PRODUCT CHARACTERISTICS

The Manufacturer/Supplier shall not guarantee the full scope of use of the product if:

- the Buyer fails to comply with the recommendations of the Manufacturer/Supplier or its instructions;
- the material is subject to mechanical damage or it loses its physical and chemical characteristics or its resistance, e.g. water resistance, UV resistance, etc. due to incorrect application of the material;
- the material is processed, e.g. printed on, combined with another material, subject to physical and chemical treatment, etc.;
- the material has been affected by mechanical force or is used incorrectly;
- the material is damaged due to unprofessional application;
- the material is misused.

SUMMARY

All IKONOS products are subject to quality control throughout the entire manufacturing process, are covered with a commercial quality warranty and are free of any manufacturing defects. Any published information on IKONOS products is based on research which the manufacturer deems reliable, even though this information is not considered a warranty. The Manufacturer/Supplier confirms the full scope of use of the product, provided the Buyer strictly observes all recommendations. As IKONOS products are suitable for a wide range of applications and are constantly developed, the Buyer should always test the given product in terms of the intended application.

The information contained herein is based on our knowledge and practical experience and may be amended without prior notice. Any information always represents the average, the minimum or the maximum value and should be treated as such. Any data presented herein is for information purposes only and shall not be the basis for any warranty.

Any possible limited liability of the Manufacturer/Supplier applies exclusively to the costs of defective material purchased by the customer. Agents, representatives or vendors shall not have the right to give any warranties, certifications, guarantees or to make representations other than those provided for herein.

The Manufacturer/Supplier shall not be responsible for any damage to substrates, surfaces or equipment resulting from use or removal of the products.

The Manufacturer/Supplier shall not be responsible for any other damage caused during the processes of application or removal of IKONOS products.

All offered IKONOS products are subject to "General Commercial Terms and Conditions" available at: <https://atrium.com.pl/wsparcie/ogolne-warunki-handlowe> or <https://ikonosmedia.eu/terms-and-conditions/>.

The Manufacturer/Supplier shall not be responsible for any accidental and/or consequential damage including, but not limited to, lost profits or revenue, other lost gains, costs of labour, costs and fees related to reconstruction of a graphic, lost production time, costs of removal of defective graphics, etc. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. Provisions of this TDS are not a commercial offer as defined in the Civil Code.